

Opening Specifications

Visions 3500 Single Hung Windows (9107/9109)

Rev 6/17



Call Size	Sq. Ft. Clear Opening	Clear Opening		Sq. Ft. Daylight Opening	Sq. Ft. Vent	Top of Subfloor to Top of Sill Stop ^a	Sq. Ft. Overall Unit Area ^b
		Width	Height				
1626	1.04	13.50	11.11	2.00	1.04	54.25	3.59
1630	1.32	13.50	14.11	2.53	1.32	48.25	4.31
1636	1.60	13.50	17.11	3.06	1.60	42.25	5.04
1640	1.89	13.50	20.11	3.58	1.89	36.25	5.77
1646	2.17	13.50	23.11	4.11	2.17	30.25	6.50
1650	2.45	13.50	26.11	4.64	2.45	24.25	7.23
1652	2.54	13.50	27.11	4.82	2.54	22.25	7.47
1656	2.73	13.50	29.11	5.17	2.73	42.25	7.96
1656 OR	2.15	13.50	22.95	5.17	2.15	42.25	7.96
1656 CO	2.23	13.50	23.82	5.17	2.23	42.25	7.96
1660	2.87	13.50	30.63	5.70	2.87	36.25	8.69
1666	2.87	13.50	30.63	6.23	2.45	30.25	9.42
1670	2.87	13.50	30.63	6.76	2.31	24.25	10.15
2026	1.50	19.50	11.11	2.94	1.50	54.25	4.81
2030	1.91	19.50	14.11	3.72	1.91	48.25	5.79
2036	2.32	19.50	17.11	4.50	2.32	42.25	6.77
2040	2.72	19.50	20.11	5.28	2.72	36.25	7.75
2046	3.13	19.50	23.11	6.06	3.13	30.25	8.73
2050	3.54	19.50	26.11	6.84	3.54	24.25	9.71
2052	3.67	19.50	27.11	7.10	3.67	22.25	10.04
2056	3.94	19.50	29.11	7.62	3.94	42.25	10.69
2056 OR	3.11	19.50	22.95	7.62	3.11	42.25	10.69
2056 CO	3.23	19.50	23.82	7.62	3.23	42.25	10.69
2060	4.15	19.50	30.63	8.39	4.15	36.25	11.67
2066	4.15	19.50	30.63	9.17	3.54	30.25	12.65
2070	4.15	19.50	30.63	9.95	3.34	24.25	13.63
2626	1.97	25.50	11.11	3.89	1.97	54.25	6.04
2630	2.50	25.50	14.11	4.92	2.50	48.25	7.27
2636	3.03	25.50	17.11	5.95	3.03	42.25	8.50
2640	3.56	25.50	20.11	6.97	3.56	36.25	9.73
2646	4.09	25.50	23.11	8.00	4.09	30.25	10.96
2650	4.62	25.50	26.11	9.03	4.62	24.25	12.19
2652	4.80	25.50	27.11	9.37	4.80	22.25	12.60
2656	5.16	25.50	29.11	10.06	5.16	42.25	13.42
2656 OR	4.06	25.50	22.95	10.06	4.06	42.25	13.42
2656 CO	4.22	25.50	23.82	10.06	4.22	42.25	13.42
2660	5.42	25.50	30.63	11.09	5.42	36.25	14.65
2666	5.42	25.50	30.63	12.12	4.63	30.25	15.88
2670	5.42	25.50	30.63	13.15	4.36	24.25	17.11
2826	2.12	27.50	11.11	4.20	2.12	54.25	6.45
2830	2.70	27.50	14.11	5.32	2.70	48.25	7.77
2836	3.27	27.50	17.11	6.43	3.27	42.25	9.08
2840	3.84	27.50	20.11	7.54	3.84	36.25	10.39
2846	4.41	27.50	23.11	8.65	4.41	30.25	11.70
2850	4.99	27.50	26.11	9.76	4.99	24.25	13.02
2852	5.18	27.50	27.11	10.13	5.18	22.25	13.45
2856	5.56	27.50	29.11	10.88	5.56	42.25	14.33
2856 OR	4.38	27.50	22.95	10.88	4.38	42.25	14.33
2856 CO	4.55	27.50	23.82	10.88	4.55	42.25	14.33
2860	5.85	27.50	30.63	11.99	5.85	36.25	15.64
2866	5.85	27.50	30.63	13.10	4.99	30.25	16.95
2870	5.85	27.50	30.63	14.21	4.70	24.25	18.27

Shaded sizes meet or exceed egress opening requirements per 2006-2015 IBC (International Building Code) minimum dimensions of 20" clear opening width, 24" clear opening height, 5.7 sq. ft. clear opening and floor to bottom of clear opening not to exceed 44".

^a Floor to bottom of clear opening dimensions are based on a 82" jamb height of a 6-10 door.

All units 66" R.O. height and over are based off 106" jamb height for floor to clear opening dimension

^b Sq. Ft. Overall Unit Area is calculated on the jamb dimension.

Opening Specifications

Visions 3500 Single Hung Windows (9107/9109)

Rev 6/17



Call Size	Sq. Ft. Clear Opening	Clear Opening		Sq. Ft. Daylight Opening	Sq. Ft. Vent	Top of Subfloor to Top of Sill Stop ^a	Sq. Ft. Overall Unit Area ^b
		Width	Height				
3026	2.43	31.50	11.11	4.83	2.43	54.25	7.27
3030	3.09	31.50	14.11	6.11	3.09	48.25	8.75
3036	3.74	31.50	17.11	7.39	3.74	42.25	10.23
3040	4.40	31.50	20.11	8.67	4.40	36.25	11.71
3046	5.06	31.50	23.11	9.95	5.06	30.25	13.19
3050	5.71	31.50	26.11	11.23	5.71	24.25	14.67
3052	5.93	31.50	27.11	11.65	5.93	22.25	15.16
3056	6.37	31.50	29.11	12.51	6.37	42.25	16.15
3056 OR	5.02	31.50	22.95	12.51	5.02	42.25	16.15
3056 CO	5.21	31.50	23.82	12.51	5.21	42.25	16.15
3060	6.70	31.50	30.63	13.78	6.70	36.25	17.63
3066	6.70	31.50	30.63	15.06	5.72	30.25	19.11
3070	6.70	31.50	30.63	16.34	5.39	24.25	20.59
3626	2.89	37.50	11.11	5.78	2.89	54.25	8.50
3630	3.68	37.50	14.11	7.31	3.68	48.25	10.23
3636	4.46	37.50	17.11	8.84	4.46	42.25	11.96
3640	5.24	37.50	20.11	10.36	5.24	36.25	13.69
3646	6.02	37.50	23.11	11.89	6.02	30.25	15.42
3650	6.80	37.50	26.11	13.42	6.80	24.25	17.15
3652	7.06	37.50	27.11	13.93	7.06	22.25	17.72
3656	7.58	37.50	29.11	14.95	7.58	42.25	18.88
3656 OR	5.98	37.50	22.95	14.95	5.98	42.25	18.88
3656 CO	6.20	37.50	23.82	14.95	6.20	42.25	18.88
3660	7.98	37.50	30.63	16.48	7.98	36.25	20.61
3666	7.98	37.50	30.63	18.01	6.80	30.25	22.34
3670	7.98	37.50	30.63	19.54	6.41	24.25	24.06
4026	3.36	43.50	11.11	6.72	3.36	54.25	9.73
4030	4.26	43.50	14.11	8.50	4.26	48.25	11.71
4036	5.17	43.50	17.11	10.28	5.17	42.25	13.69
4040	6.08	43.50	20.11	12.06	6.08	36.25	15.67
4046	6.98	43.50	23.11	13.84	6.98	30.25	17.65
4050	7.89	43.50	26.11	15.62	7.89	24.25	19.63
4052	8.19	43.50	27.11	16.21	8.19	22.25	20.29
4056	8.79	43.50	29.11	17.40	8.79	42.25	21.61
4056 OR	6.93	43.50	22.95	17.40	6.93	42.25	21.61
4056 CO	7.20	43.50	23.82	17.40	7.20	42.25	21.61
4060	9.25	43.50	30.63	19.17	9.25	36.25	23.59
4066	9.25	43.50	30.63	20.95	7.89	30.25	25.56
4070	9.25	43.50	30.63	22.73	7.44	24.25	27.54

Shaded sizes meet or exceed egress opening requirements per 2006-2015 IBC (International Building Code) minimum dimensions of 20" clear opening width, 24" clear opening height, 5.7 sq. ft. clear opening and floor to bottom of clear opening not to exceed 44".

^a Floor to bottom of clear opening dimensions are based on a 82" jamb height of a 6-10 door.

All units 66" R.O. height and over are based off 106" jamb height for floor to clear opening dimension

^b Sq. Ft. Overall Unit Area is calculated on the jamb dimension.