

Thermal Performance Data

Visions 3500 Sliding Patio Door Transom 1 Panel (9701)



US Qualification Criteria		Climate Zone	U-Value	SHGC
	As of January 2016	Northern North-Central South-Central Southern	≤ 0.30	≤ 0.40 ≤ 0.25

Canadian Qualification Criteria		Climate Zone	U-Value	or	Energy Rating
	As of February 2015	Zone 1	≤ 1.60	Air Leakage $\leq 0.3 \text{ cfm/ft}^2$	≥ 25
		Zone 2	≤ 1.40		≥ 29
		Zone 3	≤ 1.20		≥ 34

U-Value

A measurement of how much energy a material conducts. The lower the U-Value, the greater the insulating effect.

Solar Heat Gain Coefficient (SHGC)

Measures how well a window or door prevents heat from passing through it.

The lower a window or door's SHGC, the less heat it allows to pass through it.

Visible Light Transmittance

The amount of light in the visible portion of the spectrum that passes through a glazing material.

Condensation Resistance Rating

Measures how well a window resists the formation of condensation on the inside surface.

The higher the number the better resistance to condensation.

Energy Rating

A value demonstrating the balance between U-Value, SHGC and air leakage.

The higher the number, the more efficient the product.

R-Value

A measurement of how much a material resists heat transfer.

A higher R-Value means a greater insulating effect and a lower rate of heat flow out of the home.

While **R-value** measures resistance to heat transfer, **U-value** measures the rate of heat transfer.

In simple terms, **U-value** is the mathematical reciprocal of **R-value**; that is, **U = 1/R** and **R = 1/U**.

^a Total Unit calculations are derived from computer simulations that are then verified by 3rd party testing in accordance with NFRC 100, NFRC 200, and NFRC 500.

^b Published values reflect 3mm/3mm glass lite thicknesses.

ENERGY PERFORMANCE DATA												CANADIAN ENERGY PERFORMANCE DATA			CANADA ENERGY STAR v 4.1			
Grille Option	Glazing thickness	aNFRC Total Unit Calculations bGlazing Option		CPD #	U-Value	Solar Heat Gain Coefficient	Visible Light Transmittance	Condensation Resistance Rating	US ENERGY STAR V 6.0				U-Value (metric)	Maximum Air Leakage Ls/m ²	Air Infiltration/Exfiltration Average	Energy Rating		
									N	NC	SC	S						
No GIA or SDL	3/4"	Clear Insul	WEA-N-316-00469-00001	0.44	0.58	0.61	45						2.50	0.6	0.05	19		
	3/4"	Insul Low-E	WEA-N-316-00474-00001	0.31	0.31	0.53	57						1.76	0.6	0.41	19		
	3/4"	Insul Low E w/Argon	WEA-N-316-00481-00001	0.28	0.31	0.53	61	Y					1.59	0.6	0.41	22	Y	
	3/4"	Passive Solar	WEA-N-316-00470-00001	0.32	0.51	0.59	57						1.82	0.6	0.05	30	Y	Y
	3/4"	Passive Solar w/Argon	WEA-N-316-00477-00001	0.29	0.51	0.59	61	Y					1.65	0.6	0.05	33	Y	Y
	3/4"	Passive Solar Extreme	WEA-N-316-00471-00001	0.27	0.46	0.57	43	Y					1.53	0.6	0.05	33	Y	Y
	3/4"	Passive Solar Extreme w/Argon	WEA-N-316-00478-00001	0.24	0.47	0.57	47	Y					1.36	0.6	0.05	37	Y	Y
	3/4"	Zo-e-shield 5	WEA-N-316-00475-00001	0.31	0.21	0.48	58					Y	1.76	0.6	0.05	13		
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-316-00482-00001	0.27	0.21	0.48	62	Y	Y	Y	Y		1.53	0.6	0.05	19	Y	
	3/4"	Zo-e-shield 5 Extreme	WEA-N-316-00476-00001	0.26	0.20	0.47	44	Y	Y	Y	Y		1.48	0.6	0.05	19	Y	
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-316-00483-00001	0.24	0.20	0.47	48	Y	Y	Y	Y		1.36	0.6	0.05	22	Y	Y
	3/4"	Zo-e-shield 6	WEA-N-316-00593-00001	0.32	0.21	0.47	56				Y		1.82	0.6	0.05	12		
	3/4"	Zo-e-shield 6 w/ Argon	WEA-N-316-00599-00001	0.28	0.21	0.47	60		Y	Y	Y		1.59	0.6	0.05	17	Y	
	3/4"	Zo-e SafeGuard Certified	WEA-N-316-00595-00001	0.32	0.21	0.47	56				Y		1.82	0.6	0.05	12		
	3/4"	Zo-e SafeGuard Certified w/ Argon	WEA-N-316-00601-00001	0.28	0.21	0.47	60		Y	Y	Y		1.59	0.6	0.05	17	Y	
	3/4"	Insul Low-E 240	WEA-N-316-00472-00001	0.32	0.20	0.30	57				Y		1.82	0.6	0.05	12		
	3/4"	Insul Low-E 240 w/Argon	WEA-N-316-00479-00001	0.28	0.19	0.30	61		Y	Y	Y		1.59	0.6	0.05	16	Y	
	3/4"	Insul Low-E 340	WEA-N-316-00473-00001	0.31	0.14	0.29	58				Y		1.76	0.6	0.05	9		
	3/4"	Insul Low-E 340 w/Argon	WEA-N-316-00480-00001	0.28	0.14	0.29	61		Y	Y	Y		1.59	0.6	0.05	13		
	3/4"	Bronze Low E	WEA-N-316-00474-00004	0.31	0.30	0.39	57						1.76	0.6	0.05	19		
	3/4"	Bronze Low E w/Argon	WEA-N-316-00481-00004	0.28	0.30	0.39	61	Y					1.59	0.6	0.05	22	Y	
Less Than 1" GIA or SDL	3/4"	Clear Insul	WEA-N-316-00484-00001	0.44	0.52	0.54	45						2.50	0.6	0.05	15		
	3/4"	Insul Low-E	WEA-N-316-00474-00002	0.31	0.28	0.48	57						1.76	0.6	0.41	17		
	3/4"	Insul Low E w/Argon	WEA-N-316-00481-00002	0.28	0.28	0.48	61	Y					1.59	0.6	0.41	21	Y	
	3/4"	Passive Solar	WEA-N-316-00485-00001	0.32	0.46	0.52	57						1.82	0.6	0.05	27	Y	
	3/4"	Passive Solar w/Argon	WEA-N-316-00492-00001	0.29	0.46	0.52	61	Y					1.65	0.6	0.05	30	Y	Y
	3/4"	Passive Solar Extreme	WEA-N-316-00486-00001	0.27	0.42	0.51	43	Y					1.53	0.6	0.05	31	Y	Y
	3/4"	Passive Solar Extreme w/Argon	WEA-N-316-00493-00001	0.24	0.42	0.51	47	Y					1.36	0.6	0.05	34	Y	Y
	3/4"	Zo-e-shield 5	WEA-N-316-00490-00001	0.31	0.19	0.43	58				Y		1.76	0.6	0.05	12		
	3/4"	Zo-e-shield 5 w/ Argon	WEA-N-316-00497-00001	0.27	0.19	0.43	62	Y	Y	Y	Y		1.53	0.6	0.05	17	Y	
	3/4"	Zo-e-shield 5 Extreme	WEA-N-316-00491-00001	0.26	0.18	0.42	44	Y	Y	Y	Y		1.48	0.6	0.05	18	Y	
	3/4"	Zo-e-shield 5 Extreme w/ Argon	WEA-N-316-00498-00001	0.24	0.18	0.42	48	Y	Y	Y	Y		1.36	0.6	0.05	21	Y	Y
	3/4"	Zo-e-shield 6	WEA-N-316-00606-00001	0.34	0.19	0.42	56				Y		1.93	0.6	0.05	9		
	3/4"	Zo-e-shield 6 w/ Argon	WEA-N-316-00612-00001	0.30	0.19	0.42	60		Y	Y	Y		1.70	0.6	0.05	14		
	3/4"	Zo-e SafeGuard Certified	WEA-N-316-00608-00001	0.34	0.19	0.42	56				Y		1.93	0.6	0.05	9		
	3/4"	Zo-e SafeGuard Certified w/ Argon	WEA-N-316-00614-00001	0.30	0.19	0.42	60		Y	Y	Y		1.70	0.6	0.05	14		
	3/4"	Insul Low-E 240	WEA-N-316-00487-00001	0.32	0.18	0.26	57				Y		1.82	0.6	0.05	10		
	3/4"	Insul Low-E 240 w/Argon	WEA-N-316-00494-00001	0.28	0.17	0.26	61		Y	Y	Y		1.59	0.6	0.05	15		
	3/4"	Insul Low-E 340	WEA-N-316-00488-00001	0.31	0.13	0.26	58				Y		1.76	0.6	0.05	9		
	3/4"	Insul Low-E 340 w/Argon	WEA-N-316-00495-00001	0.28	0.12	0.26	61		Y	Y	Y		1.59	0.6	0.05	12		
	3/4"	Bronze Low E	WEA-N-316-00489-00002	0.31	0.27	0.35	57						1.76	0.6	0.05	17		
	3/4"	Bronze Low E w/Argon	WEA-N-316-00496-00002	0.28	0.27	0.35	61	Y					1.59	0.6	0.05	21	Y	
1" Or Over GIA or SDL	3/4"	Clear Insul	WEA-N-316-00469-00003	0.44	0.46	0.												